

Protective hose | TCT

Hose for standard applications | Mechanical Engineering / Automation / Energy | Pair-slotted | PA6 | UL94 HB light

Article:	TCT
Brand:	Interflex
Type:	Pair-slit
Material:	Polyamide PA6
Flammability:	UL94 HB light
Color:	Black
Other:	Free from halogen, phosphorus and cadmium. Non-flame propagator



Description

Protective hose | TCT PA6 is a flexible corrugated slit conduit with a medium-thick wall. The conduit allows you to lay down terminated cables in a conduit where the connector cannot pass through. It also facilitates retrofitting and maintenance.

Well suited for standard applications in:

- Machine building
- Automation & Robotics
- Renewable energy installations



Article number

Art.No	Description	Nd Ø mm	Internal Ø mm	External Ø mm	Material	Color	Unit	Mr./Ms. roll
TCT-07N	Protective hose TCT PA6	7	5.6	10.3	Polyamide 6	Black	roll	50
TCT-10N	Protective hose TCT PA6	10	8.5	13.3	Polyamide 6	Black	roll	50
TCT-13N	Protective hose TCT PA6	13	11	16	Polyamide 6	Black	roll	50
TCT-16N	Protective hose TCT PA6	16	13	19	Polyamide 6	Black	roll	50
TCT-17N	Protective hose TCT PA6	17	15.5	21.5	Polyamide 6	Black	roll	50
TCT-22N	Protective hose TCT PA6	22	19.1	25.6	Polyamide 6	Black	roll	50
TCT-23N	Protective hose TCT PA6	23	21.9	28.5	Polyamide 6	Black	roll	50
TCT-26N	Protective hose TCT PA6	26	24	31.7	Polyamide 6	Black	roll	25
TCT-29N	Protective hose TCT PA6	29	27.2	35	Polyamide 6	Black	roll	25
TCT-37N	Protective hose TCT PA6	37	32	42.5	Polyamide 6	Black	roll	25
TCT-50N	Protective hose TCT PA6	50	43.9	53.9	Polyamide 6	Black	roll	25
TCT-70N	Protective hose TCT PA6	70	62.2	79	Polyamide 6	Black	roll	10