

Multiflange | RIT

Fits Rittal products | IP65


Article:	Multiflange RIT
Brand:	
Protection class:	IP65
Material:	Halogen-free, TPE-SEBS, TPE-SEBS V0
Temperature:	-40°C to 100°C



Description

The multi-flange is adapted for Rittal products and provides an efficient solution for cable entry into Rittal enclosures.

It enables high cable density and structured installation in control cabinets and enclosures.



Article number

Art.No	Description	Cable diameter Ø mm	Width mm	Depth mm	Protection class	Color	PDF
RIT-38	Multiflange Rittal 38	24pcs 20– 28 14pcs 7 – 12	339	149	IP65	RAL7035	PDF
RIT-50	Multiflange Rittal 50	2 pcs 19–34 4 pcs 16–25 2 pcs 15–21 26 pcs 10- 15 16 pcs 6-11	330	90	IP65	RAL7035	PDF
RIT-63	Multiflange Rittal 60	4 pcs 26–35 4 pcs 15–24 4 pcs 15–21 16 pcs 10–15 39 pcs 7–12	256	149	IP65	RAL7035	PDF
RIT-96	Multiflange Rittal 96	28 pcs 7–12 52 pcs 10–15 4 pcs 15–21 8 pcs 15–25 4 pcs 26–35	339	149	IP65	RAL7035	PDF
RIT-126	Multiflange Rittal 126	1st 30–60 4 pcs 26–35 4 pcs 15–24 44 pcs 10–15 73st 7–12	301	221	IP65	RAL7035	PDF
RIT-129	Multiflange Rittal 129	1st 30–60 2 pcs 26–35 4 pcs 15–24 63 pcs 10–15 59st 7–12	447	149	IP65	RAL7035	PDF
RIT-139	Multiflange Rittal 139	1st 30–60 9 pcs 15–24 129 pcs 10–15	534	149	IP65	RAL7035	PDF

Article number

RIT-192	Multiflange Rittal 192	1st 30–60 4 pcs 26–35 4 pcs 15–24 44 pcs 10–15 139st 7–12	401	221	IP65	RAL7035	PDF
---------	---------------------------	--	-----	-----	------	---------	-----