

Cable duct Licatec | HF-L

Halogen-free slotted cable duct | RAL7035

Article:	HF-L
Brand:	Licatec
Material:	PC/ABS
Temperature:	-25°C to 90°C
Length:	2000mm
Color:	RAL7035
Other:	"cable holder in the middle of the slot from a height of 60mm.



Description

Cable duct Licatec / HF-L is a high-quality halogen-free cable duct made of PC-ABS that complies with the DIN EN 50085 standard. This innovative series is carefully manufactured from specially developed halogen-free plastic, fully in accordance with VDE 0472, part 815. A significant safety advantage is that the material does not emit any toxic gases in the event of a fire, making it particularly suitable for public environments. Licatec's cable duct has a "cable holder" in the middle of the slot from a height of 60mm.

- We also perform cuts and adjustments according to your wishes

Article number

Art.No	E-number	Description	Width	Height	Length	Pc
3030HF-L	2990499	Licatec Slotted Halogen-free	30	30	2000	32
2540HF-L	2990500	Licatec Slotted Halogen-free	25	40	2000	34
4040HF-L	2990501	Licatec Slotted Halogen-free	40	40	2000	26
6040HF-L	2990502	Licatec Slotted Halogen-free	60	40	2000	20
2560HF-L	2990503	Licatec Slotted Halogen-free	25	60	2000	30
4060HF-L	2990504	Licatec Slotted Halogen-free	40	60	2000	24
6060HF-L	2990505	Licatec Slotted Halogen-free	60	60	2000	18
8060HF-L	2990506	Licatec Slotted Halogen-free	80	60	2000	16
2580HF-L	2990507	Licatec Slotted Halogen-free	25	80	2000	28
4080HF-L	2990508	Licatec Slotted Halogen-free	40	80	2000	20
6080HF-L	2990509	Licatec Slotted Halogen-free	60	80	2000	18
8080HF-L	2990510	Licatec Slotted Halogen-free	80	80	2000	12
10080HF-L	2990511	Licatec Slotted Halogen-free	100	80	2000	12
12080HF-L	2990512	Licatec Slotted Halogen-free	120	80	2000	8
30100HF-L	2990513	Licatec Slotted Halogen-free	30	80	2000	16
40100HF-L	2990514	Licatec Slotted Halogen-free	40	100	2000	12
60100HF-L	2990515	Licatec Slotted Halogen-free	60	100	2000	16
80100HF-L	2990516	Licatec Slotted Halogen-free	80	100	2000	10
100100HF-L	2990517	Licatec Slotted Halogen-free	100	100	2000	8