

Cooling unit | Slim In

Wall-mounted | 500W - 4000W | IP54

Article:	Cooling unit Slim In
Brand:	DKC
Protection class:	IP54
Voltage:	230V 400/440V 400/460V
Effect:	500W - 4000W
Operating temperature:	20°C - 50°C 20°C - 55°C (UL)
Material:	Steel sheet Stainless steel AISI304L Acid-resistant AISI316L (on request)
Color:	RAL 7035 (steel sheet)



Description

Cooling unit / Slim In with small expansion dimensions. For wall or door mounting, with an output of 500W – 4000W.

- The cooling units are also available with UL certification.

Top version:

- 2 PLUG-IN connectors for power supply
- Control with alarm for overtemperature
- Remote ON/OFF (door contact switch)
- RS485 serial interface for remote control (ordered separately)

Other:

- Built-in "hot-pipe" loop in the condensate tray that evaporates the condensate
- Outer washable air filter
- RAL7035
- Other RALs are available
- Visual alarm
- RS485 serial protocol is available on request
- Other power supply voltage possible

Article number

Art.No	Description	Version	Capacity	Input voltage AC	Operating temperature:	Width mm	Height mm	Depth mm	Protection class	Color / Material (housing)	PDF
R5CND05021LIT	Cooling unit Slim In	Top	500W	230V	20°C-50°C	345	690	220	IP54	RAL7035	PDF
RICND05021LIT	Cooling unit Slim In INOX	Top	500W	230V	20°C-50°C	345	690	220	IP54	AISI304L	PDF
R5CND10021SIT	Cooling unit Slim In	Top	1000W	230V	20°C-50°C	490	1570	195	IP54	RAL7035	PDF
RICND10021SIT	Cooling unit Slim In INOX	Top	1000W	230V	20°C-50°C	490	1570	195	IP54	AISI304L	PDF
R5CND15021SIT	Cooling unit Slim In	Top	1500W	230V	20°C-50°C	490	1570	195	IP54	RAL7035	PDF
RICND15021SIT	Cooling unit Slim In INOX	Top	1500W	230V	20°C-50°C	490	1570	195	IP54	AISI304L	PDF
R5CND20021SIT	Cooling unit Slim In	Top	2000W	230V	20°C-50°C	490	1720	220	IP54	RAL7035	PDF
RICND20021SIT	Cooling unit Slim In INOX	Top	2000W	230V	20°C-50°C	490	1720	220	IP54	AISI304L	PDF
R5CND30021SIT	Cooling unit Slim In	Top	3000W	230V	20°C-50°C	490	1720	220	IP54	RAL7035	PDF
RICND30021SIT	Cooling unit Slim In INOX	Top	3000W	230V	20°C-50°C	490	1720	220	IP54	AISI304L	PDF
R5CND30043SIT	Cooling unit Slim In	Top	3000W	400/440V 3-phase	20°C-50°C	490	1720	220	IP54	RAL7035	PDF
RICND30043SIT	Cooling unit Slim In INOX	Top	3000W	400/440V 3-phase	20°C-50°C	490	1720	220	IP54	AISI304L	PDF
R5ULK30043SI	Cooling unit Slim In	Top UL	3000W	400/440V 3-phase	20°C-55°C	490	1720	220	IP54	RAL7035	PDF

Article number

RIULK30043SI	Cooling unit Slim In INOX	Top UL	3000W	400/440V 3- phase	20°C-55°C	490	1720	220	IP54	AISI304L	PDF
R5CND40043SO T	Cooling unit Slim In	Top	4000W	400/440V 3- phase	20°C-50°C	405	1650	220	IP54	RAL7035	PDF
RICND40043SOT	Cooling unit Slim In INOX	Top	4000W	400/440V 3- phase	20°C-50°C	405	1650	220	IP54	AISI304L	PDF