

Cable entry frame | KEL-QUICK

Divisible frame | for cables with connector | IP54

| | |
|-------------------|---|
| Article: | KEL-QUICK |
| Brand: | icotek |
| IP rating: | IP54 |
| Flammability: | UL94-V0, self-extinguishing |
| Temperature: | -40°C to 140°C |
| Material: | Polyamide |
| Mounting options: | Screw mounting, Snap-in with KEL-Snap |
| Characteristics: | UV-resistant, Silicone-free, Halogen-free, Anti-corrosive |



Description

Cable entry frame / KEL-QUICK is a compact system for entry and sealing of cables with contact, as well as for lines or pneumatic hoses using split QT entries. After filling the frame with QT grommets and cables, the cover is clamped onto the frame without the use of tools. The divisible Cable Entry Frame / KEL-QUICK can either be mounted with screws or simply snapped into the KEL-SNAP frame. A flat rubber gasket is included in the shipment.

- KEL-QUICK -B has cut-out dimensions 46 x 36 mm
- KEL-QUICK 10 for 10-pin standard industrial connectors (65 x 36 mm)
- KEL-QUICK 16 for 16-pin standard industrial connectors (86 x 36 mm)
- KEL-QUICK 24 for measuring 24-pin industrial devices.

Advantages:

- Quick assembly by "clicking" into the frame without tools or screws
- Warranties on pre-terminated cables remain in effect
- Renovations, repairs and maintenance can be done easily and quickly
- High cable density, wide variety of grommets
- Increased packing density when using double or quadruple bushings



Article number