

EMC Cable Gland | EMC-KVT-DS

Split screw connection | for shielding cables with connector | M32 / M63 | IP55

Article:	EMC-KVT-DS
Brand:	icotek
IP Rating:	IP54, IP55
Material:	Polycarbonate (conductive)
Material lock nut:	Brass, nickel-plated / Plastic
Flammability:	UL94-HB
Temperature:	40°C to 90°C



Description

EMC Cable Gland | EMC-KVT-DS is based on the icotek product KVT and is metallized to enable good current conduction.

The front cable grommet (KT) is used for strain relief and cable sealing on the cable jacket. The cable shield is contacted over 360° via the rear conductive grommet (EMC-KT).

A conductive flat gasket, which is included in the delivery, connects the cable gland to the conductive housing wall. This can be an advantage when the housing wall is not painted and therefore conductive.

The contact to the metal wall is established via the special EMC lock nut. This can be an advantage when the metal wall to which the EMC-KVT-DS is to be attached is not painted and therefore conductive.

Advantages

- Both conducted and field-bound disturbances can be reliably diverted
- Scratch-resistant surface
- Contacting the cable shield over 360°
- EMC grommets made entirely from conductive elastomer
- Very good dissipation values
- Very good shielding effect with regard to EMC tightness

Article number

Art.No	E-number	Description	Number of Cables	Maximum cable diameter	Mounting height	Cut-out Metric	Cutout Round	Size	TL	Appropriate For Efforts	Unit	Pc
99432		EMC Cable Gland EMC-KVT-DS	1	17	23	M32	32.3	M32x1.5	14	1 x KT small, 1 x EMC-KT small	st	5
99435		EMC Cable Gland EMC-KVT-DS	1	35	23	M63	63.4	M63x1.5	14	1 x KT large, 1 x EMC-KT large	st	1
99437		EMC Cable Gland EMC-KVT-DS	4	17	23	M63	63.4	M63x1.5	14	4 x KT small, 4 x EMC-KT small	st	1