

Protective hose | ECT

Hose for standard applications | Mechanical engineering / Automation / Energy | PA6 | UL94 HB light

Article:	ECT
Brand:	Interflex
Material:	Polyamide PA6
Flammability:	UL94 HB light
Temperature:	-40°C to 105°C (150°C short time)
Color:	Black
Other:	Free from halogen, phosphorus and cadmium. Non-flame propagator



Description

Protective hose / ECT is very flexible with a thin wall in PA6. The protective hose is perfect for insulation and as mechanical protection for cables. ECT has a special patented profile so that the / ORJ o-ring provides a higher IP class.

Well suited for standard applications in:

- Machine building
- Automation & Robotics
- Renewable energy installations



Article number

Art.No	Description	ND Ø mm	Internal Ø mm	External Ø mm	Material	Color	Unit	Mr./Ms. roll
ECT-07N	Protective hose ECT PA6	7	6.3	10	Polyamide 6	Black	roll	50
ECT-10N	Protective hose ECT PA6	10	9.7	13	Polyamide 6	Black	roll	50
ECT-12N	Protective hose ECT PA6	12	12.2	15.8	Polyamide 6	Black	roll	50
ECT-17N	Protective hose ECT PA6	17	16.8	21.2	Polyamide 6	Black	roll	50
ECT-23N	Protective hose ECT PA6	23	22.6	28.5	Polyamide 6	Black	roll	50
ECT-29N	Protective hose ECT PA6	29	28.3	34.5	Polyamide 6	Black	roll	50
ECT-36N	Protective hose ECT PA6	36	36.3	42.5	Polyamide 6	Black	roll	30
ECT-48N	Protective hose ECT PA6	48	47.5	54.5	Polyamide 6	Black	roll	30