

## Strain relief plate | ZL

Mounting via screw

Article:	ZL
Brand:	icotek
Material:	Polyamide
Bushing material:	Brass
Flammability:	UL94-V0, self-extinguishing
Temperature:	-40 - 140°C
Mounting method:	Screw mounting
Color:	Black (RAL 9005)
Characteristics:	Halogen-free, silicone-free



### Description

Strain relief plate / ZL is used for static or dynamic applications to organize and secure cables on machines, control panels or pull chains. The design of the strain relief unit provides safe strain relief according to EN 62444. Mounting of cables or pneumatic hoses is made easy with Cable ties.

By using aluminum (ZL-AB types) or brass (ZL-MS types) for the screw holes, a better fit of the strain relief plate is achieved, even in environments with high vibration. Strain relief plates ZL 03 | 04 | 05 have different cam widths. Thus, a multifunctional product is provided for different cable sizes.

- Use DH spacers for multi-layer installation.

Article number

Art.No	Description	Type	Mounting & Assembly	Number of Cables	Length mm L1	Length mm L2	Width mm	Height mm	Unit	Pc
32222	Drag reduction sheet ZL	39	Screw mounting	3	38.5	19.5	40	10	fingerprint	10
32224	Drag reduction sheet ZL	60	Screw mounting	4	59.5	43.5	40	10	fingerprint	10
32226	Drag reduction sheet ZL	70	Screw mounting	5	69.1	43.5	40	10	fingerprint	10
32228	Drag reduction sheet ZL	87	Screw mounting	6	86.5	68	40	10	fingerprint	10
32230	Drag reduction sheet ZL	103	Screw mounting	7	102	84	40	10	fingerprint	10
32232	Drag reduction sheet ZL	121	Screw mounting	8	121	102.5	40	10	fingerprint	10
32234	Drag reduction sheet ZL	140	Screw mounting	9	139.5	121	40	10	fingerprint	10
32236	Drag reduction sheet ZL	180	Screw mounting	12	180	157	42	11	fingerprint	10