

## Cable entry plate | KEL-DPZ-FL21

FL21 Multi-membrane | high cable density | IP65 | UL Type 12

Article:	KEL-DPZ-FL21
Brand:	icotek
Protection class:	IP65
UL Type:	UL Type 12
Flammability:	UL94-V0, self-extinguishing
Temperature:	40°C to 100°C
Material:	Elastomer
Material Base frame:	Polyamide, Stainless steel V2A
Mounting options:	Screw mounting
Characteristics:	Silicone-free, Halogen-free



### Description

The new Cable entry plate / KEL-DPZ-FL21 (IP65) has been specially developed for the standard FL21 cut-out. It can be mounted with screws or rivets as required. Screws are not included in the scope of delivery, rivets (IP54) can be ordered as an option.

- ST-B plugs can be used to seal pierced diaphragms if cables have been removed.

### Advantages

- Quick assembly
- High cable density
- Certified protection types up to IP66 (according to EN 60529)
- Automatic sealing and strain relief for the cable
- Hygienic design – free from dirt-collecting depressions
- Space-saving design



## Article number

Art.No	Description	Number of Cables	Maximum cable diameter	Length mm	Width mm	Height mm	Mounting height	Color	Punching	Cable diameter range	Unit	Pc
55550	KEL-DPZ-FL21 25 gray	25	22	216	84	5.5	5.5	grey (similar to RAL 7035)	196 x 59	4 x 5-10.2 mm   16 x 9-16.2 mm   5 x 16-22 mm	st	5
55551	KEL-DPZ-FL21 36 gray	36	22	216	84	5.5	5.5	grey (similar to RAL 7035)	196 x 59	12 x 7.2-12 mm   19 x 9-16.2 mm   1 x 16-22 mm	st	5
55560	KEL-DPZ-FL21 25 black	25	22	216	84	5.5	5.5	black	196 x 59	4 x 5-10.2 mm   16 x 9-16.2 mm   5 x 16-22 mm	st	5
55561	KEL-DPZ-FL21 36 black	36	22	216	84	5.5	5.5	black	196 x 59	12 x 7.2-12 mm   19 x 9-16.2 mm   1 x 16-22 mm	st	5