

Cooling unit | Slim Out

Wall-mounted | 1000W - 4000W | IP54

Article:	Cooling unit Slim Out
Brand:	DKC
Protection class:	IP54
Voltage:	230V 400/440V 400/460V
Effect:	1000W - 4000W
Operating temperature:	20°C - 50°C 20°C - 55°C (UL)
Material:	Steel sheet Stainless steel AISI304L Acid-resistant AISI316L (on request)
Color:	RAL 7035 (steel sheet)



Description

Cooling units / Slim Out with small installation dimensions. For wall or door mounting, with a power of 100W – 4000W. To meet the requirements of reducing the radiator protrusion, we have supplemented the RamKlima series with the SLIM series. They are particularly suitable for cooling battery cabinets and in all applications where it is necessary to have a reduced radiator size. The product line includes cooling powers from 500 to 4000 Watt (according to DIN3168).

- The cooling units are also available with UL certification.

Top version:

- 2 PLUG-IN connectors for power supply
- Control with alarm for overtemperature
- Remote ON/OFF (door contact switch)
- RS485 serial interface for remote control (ordered separately)

Other:

- Foamed polyurethane gasket on the back of the unit.
- Built-in "hot-pipe" loop in the condensate tray that evaporates the condensate water.
- External washable air filter.
- Texture coated in RAL7035.
- Other RAL colors are available.
- Visual alarm.
- RS485 serial protocol is available on request.
- Other voltage possible

Article number

Art.No	Description	Version	Capacity	Input voltage AC	Operating temperature:	Width	Height	Depth	Protection class	Color / Material (housing)	PDF
R5CND10021SOT	Cooling units Slim Out	Top	1000W	230V	20°C-50°C	405	1500	190	IP54	RAL7035	PDF
RICND10021SOT	Cooling unit Slim Out INOX	Top	1000W	230V	20°C-50°C	405	1500	190	IP54	AISI304L	PDF
R5CND15021SOT	Cooling units Slim Out	Top	1500W	230V	20°C-50°C	405	1500	190	IP54	RAL7035	PDF
RICND15021SOT	Cooling unit Slim Out INOX	Top	1500W	230V	20°C-50°C	405	1500	190	IP54	AISI304L	PDF
R5CND20021SOT	Cooling units Slim Out	Top	2000W	230V	20°C-50°C	405	1650	220	IP54	RAL7035	PDF
RICND20021SOT	Cooling unit Slim Out INOX	Top	2000W	230V	20°C-50°C	405	1650	220	IP54	AISI304L	PDF
R5CND30021SOT	Cooling units Slim Out	Top	3000W	230V	20°C-50°C	405	1650	220	IP54	RAL7035	PDF
RICND30021SOT	Cooling unit Slim Out INOX	Top	3000W	230V	20°C-50°C	405	1650	220	IP54	AISI304L	PDF
R5CND30043SOT	Cooling units Slim Out	Top	3000W	400/440V 3-phase	20°C-50°C	405	1650	220	IP54	RAL7035	PDF
RICND30043SOT	Cooling unit Slim Out INOX	Top	3000W	400/440V 3-phase	20°C-50°C	405	1650	220	IP54	AISI304L	PDF
R5ULK30043SOT	Cooling units Slim Out	Top UL	3000W	400/460V 3-phase	20°C-55°C	405	1650	220	IP54	RAL7035	PDF
RIULK30043SOT	Cooling unit Slim Out INOX	Top UL	3000W	400/460V 3-phase	20°C-55°C	405	1650	220	IP54	AISI304L	PDF
R5CND40021SOT	Cooling units Slim Out	Top	4000W	230V	20°C-50°C	405	1650	220	IP54	RAL7035	PDF

Article number

RICND40021SOT	Cooling unit Slim Out INOX	Top	4000W	230V	20°C-50°C	405	1650	220	IP54	AISI304L	PDF
R5CND40043SOT	Cooling units Slim Out	Top	4000W	400/440V 3-phase	20°C-50°C	405	1650	220	IP54	RAL7035	PDF
RICND40043SOT	Cooling unit Slim Out INOX	Top	4000W	400/440V 3-phase	20°C-50°C	405	1650	220	IP54	AISI304L	PDF