

Protective hose | TCT

Hose for standard applications | Mechanical Engineering / Automation / Energy | Pair-slotted | PA6 | UL94 HB light

Article:	TCT
Brand:	Interflex
Type:	Pair-slitt
Material:	Polyamide PA6
Flammability:	UL94 HB light
Color:	Black
Other:	Free from halogen, phosphorus and cadmium. Non-flame propagator



Description

Protective hose / TCT in PA6 is a flexible corrugated pair-slotted protective hose with medium-thick walls. The protective hose gives you the opportunity to lay connected cables in a hose where the connector cannot pass through. It also makes it easier for retrofitting and maintenance.

Well suited for standard applications in:

- Machine building
- Automation & Robotics
- Renewable energy installations



Article number

Art.No	Description	ND Ø mm	Internal Ø mm	External Ø mm	Meters	Color	Material
TCT-07N	Protective hose TCT PA6	7	5.6	10.3	50	Black	Polyamide 6
TCT-10N	Protective hose TCT PA6	10	8.5	13.3	50	Black	Polyamide 6
TCT-13N	Protective hose TCT PA6	13	11	16	50	Black	Polyamide 6
TCT-16N	Protective hose TCT PA6	16	13	19	50	Black	Polyamide 6
TCT-17N	Protective hose TCT PA6	17	15.5	21.5	50	Black	Polyamide 6
TCT-22N	Protective hose TCT PA6	22	19.1	25.6	50	Black	Polyamide 6
TCT-23N	Protective hose TCT PA6	23	21.9	28.5	50	Black	Polyamide 6
TCT-26N	Protective hose TCT PA6	26	24	31.7	25	Black	Polyamide 6
TCT-29N	Protective hose TCT PA6	29	27.2	35	25	Black	Polyamide 6
TCT-37N	Protective hose TCT PA6	37	32	42.5	25	Black	Polyamide 6
TCT-50N	Protective hose TCT PA6	50	43.9	53.9	25	Black	Polyamide 6
TCT-70N	Protective hose TCT PA6	70	62.2	79	10	Black	Polyamide 6