

## Relief plate | SF/ZL

Mounted on DIN profile | TS35

Article:	SF/ZL
Brand:	icotek
Material:	Polyamide
Mounting foot material:	Steel
Flammability:	UL94-V0, self-extinguishing
Temperature:	-40 - 140°C
Mounting method:	Snap-in
Color:	Black (RAL 9005)
Characteristics:	Halogen-free, silicone-free



### Description

Relief plate | SF/ZL used for mounting on a 35mm H-shaped DIN rail.

It can be used for strain relief of cables and conduits.

The SF|ZL range is based upon the strain relief plate ZL, which is mounted on snap-in mounting feet for 35 mm top hat rails.

### Assembly:

- 35 mm DIN rail form H

### Advantages:

- Strain relief according to EN 62444
- Fast and easy mounting
- Cost-effective solution
- High cable density
- Versatile utilisation

## Article number

Art.No	Description	Type	Mounting & Assembly	Number of Cables	Length mm	Width mm	Height mm	Mounting height mm	Unit	Pc
32351	Dragavlastningsplatta	39	Snap-in	3	38.5	51.7	16	11.4	fingerprint	10
32352	Dragavlastningsplatta  SF/ZL	60	Snap-in	4	59.5	51.7	16	11.4	fingerprint	10
32353	Dragavlastningsplatta	70	Snap-in	5	69.1	51.7	16	11.4	fingerprint	10
32354	Dragavlastningsplatta	87	Snap-in	6	86.5	51.7	16	11.4	fingerprint	10
32355	Dragavlastningsplatta	103	Snap-in	7	102.5	51.7	16	11.4	fingerprint	10
32356	Dragavlastningsplatta	121	Snap-in	8	121	51.7	16	11.4	fingerprint	10
32357	Dragavlastningsplatta	140	Snap-in	9	139.5	51.7	16	11.4	fingerprint	10
32358	Dragavlastningsplatta	180	Snap-in	12	180	51.7	16	11.4	fingerprint	10