

Cable entry plate | KEL-DPZ-CLICK

Multi-membrane Snap-In | threading M25 - M63 | IP65 - IP68

Article:	KEL-DPZ-CLICK
Brand:	icotek
Protection class:	IP54, IP55, IP64, IP65, IP66, IP67, IP68
Flammability:	UL94-V0, self-extinguishing
Temperature:	40°C to 100°C
Material:	Elastomer
Material Base frame:	Polyamide
Mounting options:	Attached with locking nut, Snap-in
Characteristics:	Silicone-free, Halogen-free



Description

Multi-membrane cable entry plate / KEL-DPZ-CLICK are designed to route and seal cables without connectors or fiber optics (from 1.5 mm to 22 mm in diameter) in limited space. The new version of the proven KEL-DPZ cable entry plates snaps directly into the cutout, which significantly reduces assembly time. The KEL-DPZ-CLICK is threaded and fits metric cutouts from M25 to M63.

Snap in:

For wall thickness: 1 – 2.5 mm

Protection class: IP65

Screwed in using a lock nut:

For wall thickness: max. 11 mm

Protection class: IP66 / IP68

The installation of KEL-DPZ-CLICK with cables or pneumatic hoses can be done quickly and easily. Just make a small hole in the thin membrane and push the cables through.

KEL-DPZ-CLICK provides strain relief and protection class IP65 / IP66 / IP68.

ST-B plugs can be used to seal pierced diaphragms if cables have been removed.

Advantages:

- Quick assembly
- Two different mounting options: with screw or "snap-in"
- High cable density



Article number

Art.No	Description	Number of Cables	Max Kabeldia.	Outer Diameter	Reaming Metric	Locknut	Cable. Interval	Color	Unit	Pc
44050	KEL-DPZ-CLICK 25 3	3	6.5	39	M25	52284	2 x 3.2-5.2 mm 1 x 3.2-6.5 mm	gray	st	10
44051	KEL-DPZ-CLICK 25 4	4	5.2	39	M25	52284	4 x 3.2-5.2 mm	gray	st	10
44052	KEL-DPZ-CLICK 32 4	4	12.5	44	M32	52285	3 x 3.2-6.5 mm 1 x 7.2-12.5 mm	gray	st	10
44053	KEL-DPZ-CLICK 32 4-2	4	9.5	44	M32	52285	4 x 5-9.5 mm	gray	st	10
44054	KEL-DPZ-CLICK 32 7	7	6.5	44	M32	52285	7 x 3.2-6.5 mm	gray	st	10
44055	KEL-DPZ-CLICK 40 8	8	10.2	52	M40	52286	4 x 3.2-6.5 mm 4 x 5-10.2 mm	gray	st	10
44056	KEL-DPZ-CLICK 50 8	8	12.5	62	M50	52287	5 x 5-10.2 mm 3 x 7.2-12.5 mm	gray	st	10
44057	KEL-DPZ-CLICK 50 10	10	22.2	62	M50	52287	7 x 3.2-6.5 mm 2 x 5-10.2 mm 1 x 16-22.2 mm	gray	st	10
44058	KEL-DPZ-CLICK 50 12	12	10.2	62	M50	52287	4 x 3.2-6.5 mm 8 x 5-10.2 mm	gray	st	10
44059	KEL-DPZ-CLICK 50 19	19	6.5	62	M50	52287	19 x 3.2-6.5 mm	gray	st	10
44060	KEL-DPZ-CLICK 50 78	78	5	62	M50	52287	76 x 1.5-2.6 mm 2 x 2.5-5 mm	gray	st	10
44061	KEL-DPZ-CLICK 63 9	9	22.2	75	M63	52288	1 x 3.2-6.5 mm 3 x 5-10.2 mm 4 x 9- 16.2 mm 1 x 16- 22.2 mm	gray	st	10

Article number

44062	KEL-DPZ-CLICK 63 13	13	16.2	75	M63	52288	4 x 3.2-6.5 mm 4 x 5-10.2 mm 5 x 9- 16.2 mm	gray	st	10
44063	KEL-DPZ-CLICK 63 14	14	10.2	75	M63	52288	14 x 5-10.2 mm	gray	st	10
44064	KEL-DPZ-CLICK 63 35	35	6.5	75	M63	52288	35 x 3.2-6.5 mm	gray	st	10