

## Soil braids | MB

Manufactured from flexible E-Cu fine-stranded conductors with connection plates 100 - 1000mm

Article:	MB
Brand:	icotek
Material:	Cu-ETP
Mounting:	Screw mounting
Mounting surface	Steel Plate
Cross-section	6 sq mm - 70 sq mm
Electrical load	67 A - 403 A



### Description

Manufactured from very flexible E-Cu fine-stranded copper conductors with tinned copper strip connectors.

The low transition and connection resistance makes them particularly suitable as ground connections.

The ground braids are available with connections for M4, M5, M6, M8, or M10, and in some versions with combined connection sizes.

The earth braids are also available with yellow/green shrink tubing (MB-GG), which provides clear visual identification.

UL Product iQ: [Download the PDF](#)

(Does not apply to MB-GG and article numbers 32868 / 32870 / 32872)

Cross-section – Current load

6 mm<sup>2</sup> – 67–80 A

10 mm<sup>2</sup> – 89–106 A


16 mm<sup>2</sup> – 132–157 A

25 mm<sup>2</sup> – 177–210 A

35 mm<sup>2</sup> – 230–275 A

50 mm<sup>2</sup> – 280–350 A

70 mm<sup>2</sup> – 338–403 A



Article number

See the side of the ice