

Power supply | CliQ M

DIN-mounted power supplies with marine certifications | Output current 3.4 to 40A | Efficiency up to 95.5% | AC input voltage | Screw terminal

Article:	CliQ M
Brand:	Delta Electronics
Input voltage AC:	85-276V 3 x 320-575V (3-Phase) 2 x 380-575V (2-Phase)
Output voltage DC:	24V
Output current	3.4A 5A 10A 20A 40A
Effect:	81.6W 120W 240W 480W 960W
Connection:	Screw connection
Other:	Marina Certificate - DNV & ABS



Description

PSU / CliQ M, mounted on DIN Rail. With its universal AC input voltage range, you can use it anywhere. The high-power, corrosion-resistant aluminum housing ensures long-term durability. The Power Boost feature gives you a 150% boost for up to 7 seconds, while Advanced Power Boost (APB) provides extra power when it's needed most. With DNV GL and ABS approvals, it is also suitable for maritime applications. In addition, it can handle extremely low temperatures down to -40°C and has a built-in DC OK contact and LED indicator for easy monitoring. All these features make the CliQ M power supply a reliable and certified choice for your needs.

- Efficiency up to 95.5%
- Universal AC input voltage range
- High power density in corrosion resistant aluminium casing
- Power Boost of 150% up to 7 seconds
- Advanced Power Boost (APB)
- DNV GL and ABS approvals for maritime applications
- Extreme low temperature cold start at -40°C
- Built-in DC OK Contact and LED indicator for DC OK/ Overload
- Conformal coating on PCBAs to protect against common dust and chemical pollutants
- Certified according to IEC/EN/UL 62368-1



Article number

Art.No	Description	Input Voltage Range	Output voltage	Output Current	Capacity	Width mm	Height mm	Depth mm	Unit	Pc
DRM-24V80W1PN	Power supply CliQ M	85-276V AC	24V DC	3.4A	81.6W	32	124	102	st	1
DRM-24V120W1PN	Power supply CliQ M	85-264V AC	24V DC	5A	120W	40	124	117	st	1
DRM-24V240W1PN	Power supply CliQ M	85-276V AC	24V DC	10A	240W	60	124	117	st	1
DRM-24V480W1PN	Power supply CliQ M	85-276V AC	24V DC	20A	480W	82	124	127	st	1
DRM-24V960W1PN	Power supply CliQ M	85-264V AC	24V DC	40A	960W	125	124	133.6	st	1
DRM-24V480W3PN	Power supply CliQ M	3 x 320-575V AC (3-Phase) 2 x 380-575V AC (2-Phase)	24V DC	20A	480W	65	124	127.1	st	1
DRM-24V960W3PN	Power supply CliQ M	3 x 320-575V AC (3-Phase) 2 x 380-575V AC (2-Phase)	24V DC	40A	960W	110	124	128.6	st	1