

## Power supply | CliQ M

DIN-mounted power supplies with marine certifications | Output current 3.4 to 40A | Efficiency up to 95.5% | AC input voltage | Screw terminal

Article:	CliQ M
Brand:	Delta Electronics
Input voltage AC:	85-276V   3 x 320-575V (3-Phase)   2 x 380-575V (2-Phase)
Output voltage DC:	24V
Output current	3.4A   5A   10A   20A   40A
Effect:	81.6W   120W   240W   480W   960W
Connection:	Screw connection
Other:	Marina Certificate - DNV & ABS



### Description

PSU / CliQ M, mounted on DIN Rail. With its universal AC input voltage range, you can use it anywhere. The high-power, corrosion-resistant aluminum housing ensures long-term durability. The Power Boost feature gives you a 150% boost for up to 7 seconds, while Advanced Power Boost (APB) provides extra power when it's needed most. With DNV GL and ABS approvals, it is also suitable for maritime applications. In addition, it can handle extremely low temperatures down to -40°C and has a built-in DC OK contact and LED indicator for easy monitoring. All these features make the CliQ M power supply a reliable and certified choice for your needs.

- Efficiency up to 95.5%
- Universal AC input voltage range
- High power density in corrosion resistant aluminium casing
- Power Boost of 150% up to 7 seconds
- Advanced Power Boost (APB)
- DNV GL and ABS approvals for maritime applications
- Extreme low temperature cold start at -40°C
- Built-in DC OK Contact and LED indicator for DC OK/ Overload
- Conformal coating on PCBAs to protect against common dust and chemical pollutants
- Certified according to IEC/EN/UL 62368-1



## Article number

Art.No	Description	Input voltage AC	Output voltage DC	Output current	Capacity	Width mm	Height mm	Depth mm	PDF
DRM-24V80W1PN	Power supply QliQ M	85-276V	24V	3.4A	81.6W	32	124	102	<a href="#">PDF</a>
DRM-24V120W1PN	Power supply QliQ M	85-264V	24V	5A	120W	40	124	117	<a href="#">PDF</a>
DRM-24V240W1PN	Power supply QliQ M	85-276V	24V	10A	240W	60	124	117	<a href="#">PDF</a>
DRM-24V480W1PN	Power supply QliQ M	85-276V	24V	20A	480W	82	124	127	<a href="#">PDF</a>
DRM-24V480W1PN	Power supply QliQ M	85-276V	24V	20A	480W	82	124	127	<a href="#">PDF</a>
DRM-24V960W1PN	Power supply QliQ M	85-264V	24V	40A	960W	125	124	133.6	<a href="#">PDF</a>
DRM-24V480W3PN	Power supply QliQ M	3 x 320-575V (3-Phase)   2 x 380-575V (2-Phase)	24V	20A	480W	65	124	127.1	<a href="#">PDF</a>
DRM-24V960W3PN	Power supply QliQ M	3 x 320-575V (3-Phase)   2 x 380-575V (2-Phase)	24V	40A	960W	110	124	128.6	<a href="#">PDF</a>