

Cable entry plate | KEL-DPR

Multi-membrane | high cable density | Up to IP65

Article:	KEL-DPR
Brand:	icotek
Protection class:	IP54, IP55, IP64, IP65
Flammability:	UL94-V0, self-extinguishing
Temperature:	40°C to 100°C
Material:	Elastomer
Material Base frame:	Polypropylene
Mounting options:	Screw mounting
Characteristics:	Halogen-free, Silicone-free



Description


Cable entry plate multi-membrane / KEL-DPR is based on the proven KEL-DP 24, but has an integrated reinforcement frame made of polypropylene. With the KEL-DPR 24, up to 48 cables from 1 to 16.1 mm can be inserted into the smallest spaces and sealed in accordance with IP65. The KEL-DPR 24 cable entry fits standard cut-outs for 24-pin connectors.

Electrical and pneumatic lines can be assembled in a matter of seconds. The corresponding membrane is perforated and the cables are simply pushed through.

- Perforated membranes can be sealed with ST-B Plugs
- A version with M4 threaded bushings is optionally available for screw assembly from the enclosure interior.

Advantages:

- Strain relief due to reinforced membrane
- Sealing in accordance with IP65
- Very quick installation
- Very high cable density
- Cables can be fed through from both sides
- Suitable for standardised cut-outs
- Optionally available with M4 threaded bushings
- Visually attractive design



Article number

Art.No	Description	Number of Cables	Max Kabeldia.	Length mm	Width mm	Height mm	Punching	Cable. Interval	Unit	Pc
46500	KEL-DPR 24 12	12	15	147	58	10.6	112 x 36	12 x 1-15 mm	st	10
46501	KEL-DPR 24 17	17	12.6	147	58	10.6	112 x 36	5 x 1-10.5 mm 12 x 1-12.6 mm	st	10
46502	KEL-DPR 24 25	25	12.1	147	58	10.6	112 x 36	18 x 1-6.5 mm 7 x 1-12.1 mm	st	10
46503	KEL-DPR 24 26	26	16.1	147	58	10.6	112 x 36	16 x 1-6.5 mm 4 x 1-12.1 mm 4 x 1-16.1 mm	st	10
46504	KEL-DPR 24 48	48	6.5	147	58	10.6	112 x 36	48 x 1-6.5 mm	st	10