

Cable gland 90° | KEL-FG-ER

Split enclosure | for cables with connector | IP65

Article:	KEL-FG-ER
Brand:	icotek
IP rating:	IP54, IP55, IP64, IP65
Flammability:	UL94-V0, self-extinguishing
Temperature:	40°C to 80°C
Material:	Polyamide
Mounting options:	Screw mounting
Characteristics:	Vibration-proof, UV-resistant, Silicone-free, Halogen-free



Description

Split flange enclosure 90° / KEL-FG-ER in IP65 are suitable for installation, sealing and strain relief of cables with connectors and wires at a 90 ° angle, enclosures, cabinets or machine walls.

Fits cable diameters from 1 to 16 mm (1-cable grommet KT 1-15) and 16 to 35 mm (single-hole grommet KT 16 – 34). The shipment includes a flat rubber gasket.

- The KEL-FG-ER-A frame fits the hole dimensions for the 24-pin standard industry connector
- The KEL-FG-ER-B frame has the hole size 36x46mm
- The KEL-FG-ER-E version is particularly suitable for flat connectors
- The small frame can be used perfectly in limited space

Advantages:

- Installation 90° from wall
- Mechanical protection for cables directly at the entrance
- Splash protection (IP65) at the starting point
- Warranties on pre-connected cables are maintained
- Strain relief according to EN 62444
- High stability, vibration resistant



Article number