

Cable entry plate | KEL-DPZ-Round

Multi-membrane | threading M25 - M63 | IP66 - IP68 | UL Type 12/4X*

Article:	KEL-DPZ-Round
Brand:	icotek
Protection class:	IP54, IP55, IP64, IP65, IP66, IP67, IP68
UL Type:	UL Type 12, UL Type 4X*
Flammability:	UL94-V0, self-extinguishing
Temperature:	-40°C to 100°C
Material:	Elastomer
Material Base frame:	Polyamide
Mounting options:	Fasten with locknut
Characteristics:	Silicone-free, Halogen-free



Description

Cable entry plate / KEL-DPZ-Round are designed to route and seal cables without connectors or fiber optics (from 1.5 mm to 22 mm in diameter) in limited space.

The KEL-DPZ round can be installed with cables or pneumatic hoses quickly and easily. Simply make a small hole in the thin membrane and push the cables through. The KEL-DPZ round provides strain relief and protection IP66 / IP68 / UL type 4X*.

- The round versions of the KEL-DPZ series have a thread that fits into metric holes from M25 to M63.
- ST-B plugs can be used to seal pierced diaphragms if cables have been removed.
- *4X for indoor use only

Advantages:

- Quick assembly
- High cable density
- Certified protection types IP66/IP68 (according to EN 60529)
- Automatic sealing and strain relief for the cable
- Suitable for metric hole punching
- Lock nut included
- Hygienic design – free from dirt-collecting depressions



Article number

Art.No	Description	Number of Cables	Max Kabeldia.	Color	Ytter Dia.	Reaming Metric	Cable. Interval	Unit	Pc
43732	KEL-DPZ 32 4	4	12.5	gray	44	M32	3 x 3.2-6.5 mm 1 x 7.2-12.5 mm	st	10
43733	KEL-DPZ 32 4-2	4	9.5	gray	44	M32	4 x 5-9.5 mm	st	10
43734	KEL-DPZ 32 7	7	6.5	gray	44	M32	7 x 3.2-6.5 mm	st	10
43736	KEL-DPZ 25 3	3	6.5	gray	39	M25	2 x 3.2-5.2 mm 1 x 3.2-6.5 mm	st	10
43737	KEL-DPZ 25 4	4	5.2	gray	39	M25	4 x 3.2-5.2 mm	st	10
43741	KEL-DPZ 40 08	8	10.2	gray	52	M40	4 x 3.2-6.5 mm 4 x 5-10.2 mm	st	10
43750	KEL-DPZ 50 8	8	12.5	gray	62	M50	5 x 5-10.2 mm 3 x 7.2-12.5 mm	st	10
43751	KEL-DPZ 50 10	10	22.2	gray	62	M50	7 x 3.2-6.5 mm 2 x 5-10.2 mm 1 x 16-22.2 mm	st	10
43752	KEL-DPZ 50 12	12	10.2	gray	62	M50	4 x 3.2-6.5 mm 8 x 5-10.2 mm	st	10
43756	KEL-DPZ 50 78	78	5	gray	62	M50	76 x 1.5-2.6 mm 2 x 2.5-5 mm	st	10
43758	KEL-DPZ 50 19	19	6.5	gray	62	M50	19 x 3.2-6.5 mm	st	10
43760	KEL-DPZ 63 9	9	22.2	gray	75	M63	1 x 3.2-6.5 mm 3 x 5-10.2 mm 4 x 9-16.2 mm 1 x 16-22.2 mm	st	10
43761	KEL-DPZ 63 13	13	16.2	gray	75	M63	4 x 3.2-6.5 mm 4 x 5-10.2 mm 5 x 9-16.2 mm	st	10

Article number

43762	KEL-DPZ 63 14	14	10.2	gray	75	M63	14 x 5-10.2 mm	st	10
43763	KEL-DPZ 80 50	35	6.5	gray	75	M63	35 x 3.2-6.5 mm	st	10
50732	KEL-DPZ 32 4	4	12.5	black	44	M32	3 x 3.2-6.5 mm 1 x 7.2-12.5 mm	st	10
50733	KEL-DPZ 32 4-2	4	9.5	black	44	M32	4 x 5-9.5 mm	st	10
50734	KEL-DPZ 32 7	7	6.5	black	44	M32	7 x 3.2-6.5 mm	st	10
50736	KEL-DPZ 25 3	3	6.5	black	39	M25	2 x 3.2-5.2 mm 1 x 3.2-6.5 mm	st	10
50737	KEL-DPZ 25 4	4	5.2	black	39	M25	4 x 3.2-5.2 mm	st	10
50741	KEL-DPZ 40 08	8	10.2	black	52	M40	4 x 3.2-6.5 mm 4 x 5-10.2 mm	st	10
50750	KEL-DPZ 50 8	8	12.5	black	62	M50	5 x 5-10.2 mm 3 x 7.2-12.5 mm	st	10
50751	KEL-DPZ 50 10	10	22.2	black	62	M50	7 x 3.2-6.5 mm 2 x 5-10.2 mm 1 x 16-22.2 mm	st	10
50752	KEL-DPZ 50 12	12	10.2	black	62	M50	4 x 3.2-6.5 mm 8 x 5-10.2 mm	st	10
50756	KEL-DPZ 50 78	78	5	black	62	M50	76 x 1.5-2.6 mm 2 x 2.5-5 mm	st	10
50758	KEL-DPZ 50 19	19	6.5	black	62	M50	19 x 3.2-6.5 mm	st	10
50760	KEL-DPZ 63 9	9	22.2	black	75	M63	1 x 3.2-6.5 mm 3 x 5-10.2 mm 4 x 9-16.2 mm 1 x 16-22.2 mm	st	10

Article number

50761	KEL-DPZ 63 13	13	16.2	black	75	M63	4 x 3.2-6.5 mm 4 x 5-10.2 mm 5 x 9- 16.2 mm	st	10
50762	KEL-DPZ 63 14	14	10.2	black	75	M63	14 x 5-10.2 mm	st	10
50763	KEL-DPZ 80 50	35	6.5	black	75	M63	35 x 3.2-6.5 mm	st	10