

## Cable gland 90° | KVT-W90

Split screw connection | for cables with connector | M32 | M50 | IP54

Article:	KVT-W90
Brand:	icotek
Protection class:	IP54
UL Type:	UL Type 12
Flammability:	UL94-V0, self-extinguishing
Temperature:	30°C to 100°C
Material:	Polycarbonate
Mounting options:	Fasten with locknut
Characteristics:	Halogen-free, Silicone-free



### Description

Cable gland 90° / KVT-W90 used to insert and seal sealed cables and wires at a 90° angle.

In particular, the KVT 50-W90 is perfectly suited to hold corrugated or smooth hoses. A large number of cable entry grommets is available to the user. By using multi-hole grommets up to 16 lines can be routed with one cable gland. Polyamide standard locknuts as well as a sealing ring are included in the shipment. Split locknuts can be ordered separately.



### Advantages:

- Cable entry with or without contact
- Warranties on pre-connected cables are maintained
- Remodeling, repairs and maintenance can be done much easier and faster
- High cable density, wide variety of grommets
- Suitable for metric hole punching
- Lock nut included
- Increased packing density when using double or quadruple bushings

## Article number

Art.No	Description	Size	Number of Cables	Maximum cable diameter	Height mm	Mounting height	Hole Saw Round	TL	Suitable for interventions	Protection class	Color	Unit	Pc
45404	Cable gland 90°   KVT-W90	M32	4	17	40 mm	26 mm	32.3 mm	11.5 mm	1 x KT small	IP54	gray	st	10
45406	Cable gland 90°   KVT-W90	M32	4	17	40 mm	26 mm	32.3 mm	11.5 mm	1 x KT small	IP54	black	st	10
45424	Cable gland 90°   KVT-W90	M50	16	17	61 mm	46.5 mm	50.4 mm	11.5 mm	4 x KT small	IP54	gray	st	5
45426	Cable gland 90°   KVT-W90	M50	16	17	61 mm	46.5 mm	50.4 mm	11.5 mm	4 x KT small	IP54	black	st	5
45414	Cable gland 90°   KVT-W90	M50	1	35	61 mm	46.5 mm	50.4 mm	11.5 mm	1 x KT large	IP54	gray	st	5
45416	Cable gland 90°   KVT-W90	M50	1	35	61 mm	46.5 mm	50.4 mm	11.5 mm	1 x KT large	IP54	black	st	5