

Cable duct Unex | 88 HFT

Halogen-free installation duct | U43X | RAL7035

Article:	88 HFT
Brand:	Unex
Material:	U43X base raw material PC
Temperature:	-45°C to 90°C
Length:	2000mm
Color:	RAL7035
Approvals:	CE, UL, CSA, N, NF, VDE, Bureau Veritas, Germanisher Loyd, FSR (Russia)



Description

Cable duct Solid Unex / HFT – Optimal solution for elevator assembly and machine installations.

Are you looking for a halogen-free, solid cable duct that meets the requirements of modern electrical installations? Then our cable duct in PC blend U43X is the obvious choice. This tight cable duct is specially designed to deliver the highest safety, functionality and finish – without compromise.

With its smooth and clean design, completely free of rough edges, it provides a professional installation that is both fast and gentle on cables. It is easy to assemble and adapted to meet the strictest requirements in, among other things, elevator assembly, electrical cabinets and control systems.

Advantages of halogen-free solid cable duct U43X:

- Made in PC blend U43X – durable, stable and halogen-free
- Self-extinguishing and certified to the highest industry standards
- Unique surface finish – no sharp edges that damage cable insulation
- Optimal for elevators, machine installations and sensitive environments
- Easy assembly saves time and reduces installation errors

This halogen-free duct is tested to meet both national and international requirements – and is a long-term solution for safe and efficient cable routing.

Buy solid cable duct U43X from C-Pro today - a safe and sustainable investment for professional installers.

Contact Us Please contact us if you have any questions or would like to customize it to your needs!

Article number

Art.No	E-number	Description	Designation 2	Width mm	Height mm	Length mm	Material	Color	Unit	Pc
6040HFT	2990017	Cable trunking Unex	Solid 40.60.88NP	60	40	2000	U43X	RAL7035	fingerprint	12