

## Cable entry plate | KEL-DPZ-CLICK

Multi-membrane Snap-In | threading M25 - M63 | IP65 - IP68

Article:	KEL-DPZ-CLICK
Brand:	icotek
Protection class:	IP54, IP55, IP64, IP65, IP66, IP67, IP68
Flammability:	UL94-V0, self-extinguishing
Temperature:	40°C to 100°C
Material:	Elastomer
Material Base frame:	Polyamide
Mounting options:	Attached with locking nut, Snap-in
Characteristics:	Silicone-free, Halogen-free



### Description

Multi-membrane cable entry plate / KEL-DPZ-CLICK are designed to route and seal cables without connectors or fiber optics (from 1.5 mm to 22 mm in diameter) in limited space. The new version of the proven KEL-DPZ cable entry plates snaps directly into the cutout, which significantly reduces assembly time. The KEL-DPZ-CLICK is threaded and fits metric cutouts from M25 to M63.

Snap in:

For wall thickness: 1 – 2.5 mm

Protection class: IP65

Screwed in using a lock nut:

For wall thickness: max. 11 mm

Protection class: IP66 / IP68

The installation of KEL-DPZ-CLICK with cables or pneumatic hoses can be done quickly and easily. Just make a small hole in the thin membrane and push the cables through.

KEL-DPZ-CLICK provides strain relief and protection class IP65 / IP66 / IP68.

ST-B plugs can be used to seal pierced diaphragms if cables have been removed.

Advantages:

- Quick assembly
- Two different mounting options: with screw or "snap-in"
- High cable density



Article number

Read more at icotek