

## Thermoelectric dehumidifier

For dehumidifying enclosures & small control panels | IP56

Article:	TG 3039
Brand:	Seifert
Housing material:	PC UL94V-0
IP rating:	IP56
Temperature:	0°C - 65°C
Color:	Black
Approvals:	WHAT, cURus
Condensation rate 30°C / 80%rH:	25 ml/h



### Description

Protect your enclosures and control panels from moisture with our Thermoelectric Dehumidifier – a maintenance-free solution for both indoor and outdoor use. Flexible mounting options and a robust design with protection class IP 56 make this an optimal choice for all applications that require reliable dehumidification. For an extra dimension of convenience, a condensate pump is an option that streamlines the handling of condensate water.

- Our Thermoelectric Dehumidifier ensures a dry environment for your valuable components, extending their life and reliability.
- condensate pump optional



## Article number

Art.No	Description	Type	Input voltage DC	Width mm	Height mm	Depth mm	Protection class	Color	PDF
3039303	Thermoelectric dehumidifier	Standard	24V	136	176	72+61	IP56	Black	<a href="#">PDF</a>
3039309	Thermoelectric dehumidifier	With integrated condensate pump	24V	136	176	148	IP56	Black	<a href="#">PDF</a>
1019305	Mounting frame	For thermoelectric dehumidifier							<a href="#">PDF</a>
AC-TG-6XXX-M-01	Drain socket	For use on the underside							<a href="#">PDF</a>