

## Cable entry plate | KEL-DPZ-Round

Multi-membrane | threading M25 - M63 | IP66 - IP68 | UL Type 12/4X\*

Article:	KEL-DPZ-Round
Brand:	icotek
Protection class:	IP54, IP55, IP64, IP65, IP66, IP67, IP68
UL Type:	UL Type 12, UL Type 4X*
Flammability:	UL94-V0, self-extinguishing
Temperature:	-40°C to 100°C
Material:	Elastomer
Material Base frame:	Polyamide
Mounting options:	Fasten with locknut
Characteristics:	Silicone-free, Halogen-free



### Description

Cable entry plate / KEL-DPZ-Round are designed to route and seal cables without connectors or fiber optics (from 1.5 mm to 22 mm in diameter) in limited space.

The KEL-DPZ round can be installed with cables or pneumatic hoses quickly and easily. Simply make a small hole in the thin membrane and push the cables through. The KEL-DPZ round provides strain relief and protection IP66 / IP68 / UL type 4X\*.

- The round versions of the KEL-DPZ series have a thread that fits into metric holes from M25 to M63.
- ST-B plugs can be used to seal pierced diaphragms if cables have been removed.
- \*4X for indoor use only

### Advantages:

- Quick assembly
- High cable density
- Certified protection types IP66/IP68 (according to EN 60529)
- Automatic sealing and strain relief for the cable
- Suitable for metric hole punching
- Lock nut included
- Hygienic design – free from dirt-collecting depressions



Article number

Read more at icotek