

## Cable entry plate | KEL-DPU

Multi-membrane | robust, strong strain relief | IP66 - IP68 | UL Type 12/4X\*

Article:	KEL-DPU
Brand:	icotek
Protection class:	IP54, IP55, IP64, IP65, IP66, IP67, IP68
UL Type:	UL Type 12, UL Type 4X*
Flammability:	UL94-V0, self-extinguishing
Temperature:	40°C to 100°C
Material:	Elastomer
Material Base frame:	Polypropylene
Mounting options:	Screw type mounting, Snap-in
Characteristics:	Silicone-free, Halogen-free



### Description

Cable entry plate / KEL-DPU are designed to route and seal cables without connectors (from 3.2 mm to 20.5 mm in diameter) in confined spaces with IP65 / IP66 / up to UL Type 4X\* ratings.

The KEL-DPU is particularly characterized by its fixed robust frame and the increased strain relief.

KEL-DPU 24 matches exact hole dimensions for 24-pin standard industrial connectors.

The installation of the Cable Entry Plate Multi-Membrane / KEL-DPU with cables or pneumatic hoses can be done quickly and easily. Simply by making a small hole in the thin membrane and then pushing the cables through.

- ST-B Plugs can be used for sealing in the membrane when cables have been removed.
- \*4X for indoor use only

### Advantages:

- High stability, vibration resistant
- Quick and easy assembly
- High cable density
- Certified protection types IP66/IP68 (according to EN 60529)
- Hygienic design – free from dirt-collecting depressions



Article number

Read more at icotek